



**4 Type**

- A** without bores (only in Stainless Steel NI)
- B** with through-holes
- C** with countersunk holes

**2**

**3**

$l_1$	$l_2$ square	1,5x elongated	$d_1$	$d_2$	$d_3$	$d_4$	$m_1$	$m_2$	$m_3$	$s$
30	30	45	3	3,2	4	6,4	18	18	16,5	1,5
40	40	60	4	4,2	5	8,3	25	25	22,5	2
50	50	75	6	5,2	5	8,3	30	30	27,5	2
60	60	90	6	5,2	5	8,3	36	36	33	2

**Specification**

- Steel **ST**
  - only type B and C
  - zinc plated, blue passivated
- Stainless Steel AISI 304 **NI**
  - all types
- Pin
  - Stainless Steel AISI 304
  - riveted
- *Stainless Steel characteristics* → Page 1489
- *Load rating information* → Page 1459
- **RoHS compliant**

**1**

**Information**

GN 136 sheet metal hinges are available in many different versions and are suitable for light to medium-duty applications.

Type A can be fixed in place by welding or by using holes made by the customer.

see also...

- *List of hinge types* → Page 956 ff.
- *Sheet metal hinges GN 136 (horizontally elongated)* → New products

**How to order**

**GN 136-NI-40-40-A**

- 1 Material**
- 2**  $l_1$
- 3**  $l_2$
- 4 Type**