



ELESA original design VRTP-P+I-SST



Inox
Stainless
Steel



iF product
design
award

2 Bore code

- B** without keyway
- K** with keyway

4 Type

- R** with revolving handle

1

3

d ₁	d ₂ H7	d ₃	d ₄	d ₅	b	l ₁	l ₂	l ₃	r	Ø Handle
80	8	18	20,5	25	18	17	35	45	29	16
100	10	18	20,5	25,5	20	17	37	60	37	18
125	12	22	26	31	22	22	44	65	48	22
160	14	26	31	40	25	27	51	80	65	23
200	16	30	36	48,5	28	34	61	80	84	24

Specification

- Plastic
Technopolymer (Polypropylene PP)
- certified in accordance with FDA
- reinforced, shock-resistant
- temperature resistant up to 80 °C
- black, matte
- Hub bushing
Stainless Steel AISI 304
- Hub cover
- Stainless Steel AISI 304
- self-adhesive
- Revolving handle
- Plastic, Technopolymer (Polyamide PA)
black, matte, certified in acc. with FDA
- Spindle
Stainless Steel AISI 304
- Keyway P9 DIN 6885 → Page 1420
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Plastic characteristics → Page 1483
- Stainless Steel characteristics → Page 1489
- RoHS compliant

Information

Elegant design taking account of ergonomic and hygienic requirements are the outstanding features of spoked handwheels GN 522.5.

Owing to the materials used, they are especially suitable for use in corrosive atmospheres or in areas which must be wet cleaned. In particular, the FDA certified plastic materials allow the use in the food industry.

see also...

- Countersunk washers GN 184.5 (for axial fixing) → Page 814

How to order

GN 522.5-125-B12-R

- 1 d₁
- 2 Bore code
- 3 d₂
- 4 Type