



ELESA Original design VB.639/VB.639 S



3 Type

- E** with threaded blind bore
- D** with threaded through bore

1 2 2

GN 5330

d ₁	d ₂ Type E		d ₃ Type D		d ₄	d ₅	d ₆	h ₁	h ₂	Length l	t min.
45	M 6	-	M 6	-	19	8	9	25	22,5	12	13
45	M 8	-	M 8	-	19	11	10	25	22,5	12	13
63	M 8	-	-	-	26	-	-	28	25	-	15
63	M 10	-	M 10	M 12	26	16	13	28	25	21	17
80	M 10	M 12	M 12	-	32	18	17	35	30	25	17
100	M 12	M 14	M 16	-	36	20	19	42	36	31	20
130	M 16	-	M 16	-	43	24	22	47	40	34	22

1 2

GN 5330.5

d ₁	d ₂ Type E	d ₄	h ₁	h ₂	t min.
45	M 6	19	25	22,5	12
63	M 8	26	28	25	15
80	M 10	32	35	30	17
100	M 12	36	42	36	20
130	M 16	43	47	40	22

Specification

- Plastic Technopolymer (Polyamide PA)
 - glass fiber reinforced
 - temperature resistant up to 130 °C
 - black, matte

GN 5330

Bushing
Brass

GN 5330.5

Bushing
Stainless Steel AISI 303

• Plastic characteristics → Page 1483

• Stainless Steel characteristics → Page 1489

• RoHS

On request

- with bore H9

Information

Tristar knobs GN 5330 / GN 5330.5 have been developed for heavy duty applications. Due to its shape, higher torque can be achieved.

see also...

- Stainless Steel-Tristar knobs GN 5345 → Page 428

How to order (Bushing brass)

1 2 3
GN 5330-80-M12-D

- 1 d₁
- 2 d₃ (d₂)
- 3 Type

How to order (Bushing Stainless Steel)

1 2 3
GN 5330.5-63-M8-E

- 1 d₁
- 2 d₂
- 3 Type