



ROSTFREI  
Inox  
Stainless  
Steel

<sup>1</sup> d <sub>1</sub>	<sup>2</sup> d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	h <sub>3</sub> min.
40	M 8	16	8,4	26	13	24
50	M 10	20	10,5	34	17	30
63	M 12	26	13	42	21	37

**Specification**

- Plastic Technopolymer (Polyamide PA)
    - shock-resistant
    - black, matte
  - Bushing
    - Steel
    - zinc plated, blue passivated
    - Stainless Steel
- NI**
- Plastic characteristics → Page 1483
  - Stainless Steel characteristics → Page 1489
  - RoHS

**Information**

Quick release star knobs GN 6336.3 are used in such applications where the knob has to be completely removed after the releasing operation and refitted rapidly for re-clamping.

The knob is tilted over the threaded spindle. When in position, the knob is brought into a straight position for meshing of the two threads on nut and spindle. The knob will then have to be turned only by fraction of a rotation to achieve clamping.

Functional safety exists only if the clamping surface lies at a right angle to the threaded bolt.

see also...

- Quick release knurled nuts GN 6303.1 → Page 462

How to order	<sup>1</sup> <sup>2</sup>	1 d <sub>1</sub>
	<b>GN 6336.3-50-M10</b>	2 d <sub>2</sub>

How to order	<sup>1</sup> <sup>2</sup> <sup>3</sup>	1 d <sub>1</sub>
	<b>GN 6336.3-40-M8-NI</b>	2 d <sub>2</sub>
		3 Material (bushing)