



**3 Type**  
**D** with female thread  
**E** with threaded stud

1

2

2

d <sub>1</sub>	d <sub>2</sub> Type D	d <sub>3</sub> Type E	d <sub>4</sub>	d <sub>5</sub>	h	Length l	t min.
20	M 5	M 5	14	14,8	24	10	7
25	M 6	M 6	16	16,8	29	12	9
32	M 8	M 8	18	18,8	37	14	12

**Specification**

4

- Stainless Steel
  - AISI 316 L (A4)
  - matte (Ra < 0.8 µm)
  - polished (Ra < 0.8 µm)
- Sealing ring
  - hydrogenated acrylonitrile butadiene rubber (H-NBR)
  - blue
  - temperature resistant -25 °C to +150 °C
  - Hardness 85 ±5 Shore A
  - FDA compliant
- Elastomer characteristics → Page 1483
- Stainless Steel characteristics → Page 1489
- RoHS compliant

MT  
PL

**Information**

GN 75.6 waist shaped Stainless Steel-Knobs are intended for use in hygiene areas. The sealed mounting surface enables mounting without dead spaces; the impervious geometry in combination with the high quality finish prevents the accumulation of dirt and facilitates cleaning.

GN 75.6 waist shaped Stainless Steel-Knobs have a compact and timeless design.

see also...

- Product family *Hygienic Design* → Page 16 / 18
- Sealing rings *Hygienic Design* GN 7600 → Page 881

How to order

1 2 3 4  
**GN 75.6-25-M8-E-MT**

- 1 d<sub>1</sub>
- 2 d<sub>3</sub> (d<sub>2</sub>)
- 3 Type
- 4 Finish